



<b>Dati tecnici / Technical data</b>								
Modello Model		<b>KT15.5</b>	<b>KT17.5</b>	<b>KT17.6</b>	<b>KT20.5</b>	<b>KT20.6</b>	<b>KT30.5</b>	<b>KT40.5</b>
Resa frigorifera DIN3168 (L35L35) Refrigerating yield DIN3168 (L35L35)	W	1.360	1.720	1.720	2000	2000	2800	3800
Potenza totale assorbita Total absorbed power	W	632	900	900	1.015	1.330	1.330	1.680
Alimentazione elettrica standard Standard power supply		230 V monofase / single-phase						
Frequenza Frequency	Hz	50	50	60	50	60	50	50
Corrente assorbita allo spunto Absorbed current at pick-up	A	15	21,5	21,5	24,2	24,2	35	36
Corrente assorbita a regime Absorbed current in steady conditions	A	3,6	4,5	4,5	5	5	8	8,8
Protezione amperometrica Ammetric protection	A	6	8	8	8	8	16	16
Portata aria evaporatore Evaporator air rate of flow	m <sup>3</sup> /h	550	550	550	965	965	965	965
Portata aria condensatore Condenser air rate of flow	m <sup>3</sup> /h	965	965	965	965	965	1500	1500
Grado di protezione lato quadro Protection degree – Board side		IP54	IP54	IP54	IP54	IP54	IP54	IP54
Gas refrigerante (standard) Cooling gas (standard)		R134A	R134A	R134A	R134A	R134A	R134A	R134A
Temperatura esterna ammessa Admitted outside temperature	°C	20-55	20-55	20-55	20-55	20-55	20-55	20-55
Rumorosità Noise	dB(A)	62	62	62	65	65	65	65
Peso approssimativo Approx. weight	kg	28	30	30	48	48	50	52
Dimensioni:	A	mm	301	301	301	409	409	409
Sizes:	B	mm	604	604	604	804	804	804
	C	mm	401	401	401	403	403	403